


Typical Applications

- Airports
- Highways
- Motor racing circuits
- Gas stations
- Docks & ports
- Military bases
- Truck stops

Heavy duty MDPE slot drain systems



Qmax Systems


Pavement Beam allows high level services to pass through the inlet without the need to reroute around the drainage system.



Patented Pavement Beam Feature allowing an unbroken reinforced slab to be cast around and through the inlet without interrupting the line of the inlet slot.

ACO 4x4x4 catch basin or similar allows access to the system for maintenance and discharge to the stormwater sewer.

Choice of closing and blanking end plates for each system.



Q-Guard ductile iron ADA compliant tops



Q-Flow galv. steel high capacity tops



Q-Guard galv. steel tops

Choice of ADA compliant and high intake tops.



Catch basin connectors to fit male or female channel ends.



System connectors provide seamless connection between different sized systems.



Qmax 365	Part No	Overall width in (mm)	Internal width in (mm)	Weight lbs
Channels - 2m (78.75")				
Q-Guard ductile iron rail	32821	25.0" (635)	14.4" (365)	91.5
Q-Flow galvanized steel	32822	25.0" (635)	14.4" (365)	78.3
Q-Guard galvanized steel	32823	25.0" (635)	14.4" (365)	72.8
Accessories				
Closing end plate ¹	32825	-	-	7.7
Closing end cap ²	32886	-	-	4.6
System connector plate ³	32882	-	-	5.5
Catch basin connector (m)	44360	-	-	12.5
Catch basin connector (f)	44361	-	-	12.8



Qmax 465	Part No	Overall width in (mm)	Internal width in (mm)	Weight lbs
Channels - 2m (78.75")				
Q-Guard ductile iron rail	32831	25.0" (635)	14.4" (365)	105.4
Q-Flow galvanized steel	32832	25.0" (635)	14.4" (365)	92.2
Q-Guard galvanized steel	32833	25.0" (635)	14.4" (365)	86.7
Accessories				
Closing end plate ¹	32835	-	-	10.8
Closing end cap ²	32887	-	-	6.8
System connector plate ⁴	32883	-	-	8.1
Catch basin connector (m)	44362	-	-	16.9
Catch basin connector (f)	44363	-	-	17.2



ACO Qmax 465

Qmax 600	Part No	Overall width in (mm)	Internal width in (mm)	Weight lbs
Channels - 2m (78.75")				
Q-Guard ductile iron rail	32841	25.0" (635)	14.4" (365)	139.0
Q-Flow galvanized steel	32842	25.0" (635)	14.4" (365)	125.8
Q-Guard galvanized steel	32843	25.0" (635)	14.4" (365)	120.3
Accessories				
Closing end plate ¹	32845	-	-	21.6
Closing end cap ²	32888	-	-	10.8
Catch basin connector (m)	44364	-	-	27.1
Catch basin connector (f)	44365	-	-	27.5



ACO Qmax 600

Notes:

1. Fits male or female end of uncut channels - screws in place (screws supplied)
2. Easy push fit cap for cut channel ends
3. Seamlessly connects Qmax365 male end to Qmax465 female end
4. Seamlessly connects Qmax465 male end to Qmax600 female end

ACO Polymer Products, Inc.

East Sales Office

P.O. Box 245
Chardon, OH 44024
Tel: (440) 285-7000
Toll free: (800) 543-4764
Fax: (440) 285-7005

West Sales Office

P.O. Box 12067
Casa Grande, AZ 85230
Tel: (520) 421-9988
Toll Free: (888) 490-9552
Fax: (520) 421-9899

Electronic Contact:

info@acousa.com
www.acousa.com



Follow us on

